

Sinewerttabelle für 26 inch (660,4000 mm) Abstand der Pfeilauflagen und 2 lbs (907,1847 g) Gewicht
 Formel: 0,5200 inch (13,2080 mm) * 50 lbs = Spinewert in lbs Durchbiegung des Schafts in inch / mm

| | |
|--|--|
| 20 lbs = 9,0718 kg = 33,0200 mm = 1,3000 inch | 56 lbs = 25,4012 kg = 11,7929 mm = 0,4643 inch |
| 21 lbs = 9,5254 kg = 31,4476 mm = 1,2381 inch | 57 lbs = 25,8548 kg = 11,5860 mm = 0,4561 inch |
| 22 lbs = 9,9790 kg = 30,0182 mm = 1,1818 inch | 58 lbs = 26,3084 kg = 11,3862 mm = 0,4483 inch |
| 23 lbs = 10,4326 kg = 28,7130 mm = 1,1304 inch | 59 lbs = 26,7619 kg = 11,1932 mm = 0,4407 inch |
| 24 lbs = 10,8862 kg = 27,5167 mm = 1,0833 inch | 60 lbs = 27,2155 kg = 11,0067 mm = 0,4333 inch |
| 25 lbs = 11,3398 kg = 26,4160 mm = 1,0400 inch | 61 lbs = 27,6691 kg = 10,8262 mm = 0,4262 inch |
| 26 lbs = 11,7934 kg = 25,4000 mm = 1,0000 inch | 62 lbs = 28,1227 kg = 10,6516 mm = 0,4194 inch |
| 27 lbs = 12,2470 kg = 24,4593 mm = 0,9630 inch | 63 lbs = 28,5763 kg = 10,4825 mm = 0,4127 inch |
| 28 lbs = 12,7006 kg = 23,5857 mm = 0,9286 inch | 64 lbs = 29,0299 kg = 10,3188 mm = 0,4063 inch |
| 29 lbs = 13,1542 kg = 22,7724 mm = 0,8966 inch | 65 lbs = 29,4835 kg = 10,1600 mm = 0,4000 inch |
| 30 lbs = 13,6078 kg = 22,0133 mm = 0,8667 inch | 66 lbs = 29,9371 kg = 10,0061 mm = 0,3939 inch |
| 31 lbs = 14,0614 kg = 21,3032 mm = 0,8387 inch | 67 lbs = 30,3907 kg = 9,8567 mm = 0,3881 inch |
| 32 lbs = 14,5150 kg = 20,6375 mm = 0,8125 inch | 68 lbs = 30,8443 kg = 9,7118 mm = 0,3824 inch |
| 33 lbs = 14,9685 kg = 20,0121 mm = 0,7879 inch | 69 lbs = 31,2979 kg = 9,5710 mm = 0,3768 inch |
| 34 lbs = 15,4221 kg = 19,4235 mm = 0,7647 inch | 70 lbs = 31,7515 kg = 9,4343 mm = 0,3714 inch |
| 35 lbs = 15,8757 kg = 18,8686 mm = 0,7429 inch | 71 lbs = 32,2051 kg = 9,3014 mm = 0,3662 inch |
| 36 lbs = 16,3293 kg = 18,3444 mm = 0,7222 inch | 72 lbs = 32,6586 kg = 9,1722 mm = 0,3611 inch |
| 37 lbs = 16,7829 kg = 17,8486 mm = 0,7027 inch | 73 lbs = 33,1122 kg = 9,0466 mm = 0,3562 inch |
| 38 lbs = 17,2365 kg = 17,3789 mm = 0,6842 inch | 74 lbs = 33,5658 kg = 8,9243 mm = 0,3514 inch |
| 39 lbs = 17,6901 kg = 16,9333 mm = 0,6667 inch | 75 lbs = 34,0194 kg = 8,8053 mm = 0,3467 inch |
| 40 lbs = 18,1437 kg = 16,5100 mm = 0,6500 inch | 76 lbs = 34,4730 kg = 8,6895 mm = 0,3421 inch |
| 41 lbs = 18,5973 kg = 16,1073 mm = 0,6341 inch | 77 lbs = 34,9266 kg = 8,5766 mm = 0,3377 inch |
| 42 lbs = 19,0509 kg = 15,7238 mm = 0,6190 inch | 78 lbs = 35,3802 kg = 8,4667 mm = 0,3333 inch |
| 43 lbs = 19,5045 kg = 15,3581 mm = 0,6047 inch | 79 lbs = 35,8338 kg = 8,3595 mm = 0,3291 inch |
| 44 lbs = 19,9581 kg = 15,0091 mm = 0,5909 inch | 80 lbs = 36,2874 kg = 8,2550 mm = 0,3250 inch |
| 45 lbs = 20,4117 kg = 14,6756 mm = 0,5778 inch | 81 lbs = 36,7410 kg = 8,1531 mm = 0,3210 inch |
| 46 lbs = 20,8652 kg = 14,3565 mm = 0,5652 inch | 82 lbs = 37,1946 kg = 8,0537 mm = 0,3171 inch |
| 47 lbs = 21,3188 kg = 14,0511 mm = 0,5532 inch | 83 lbs = 37,6482 kg = 7,9566 mm = 0,3133 inch |
| 48 lbs = 21,7724 kg = 13,7583 mm = 0,5417 inch | 84 lbs = 38,1018 kg = 7,8619 mm = 0,3095 inch |
| 49 lbs = 22,2260 kg = 13,4776 mm = 0,5306 inch | 85 lbs = 38,5553 kg = 7,7694 mm = 0,3059 inch |
| 50 lbs = 22,6796 kg = 13,2080 mm = 0,5200 inch | 86 lbs = 39,0089 kg = 7,6791 mm = 0,3023 inch |
| 51 lbs = 23,1332 kg = 12,9490 mm = 0,5098 inch | 87 lbs = 39,4625 kg = 7,5908 mm = 0,2989 inch |
| 52 lbs = 23,5868 kg = 12,7000 mm = 0,5000 inch | 88 lbs = 39,9161 kg = 7,5045 mm = 0,2955 inch |
| 53 lbs = 24,0404 kg = 12,4604 mm = 0,4906 inch | 89 lbs = 40,3697 kg = 7,4202 mm = 0,2921 inch |
| 54 lbs = 24,4940 kg = 12,2296 mm = 0,4815 inch | 90 lbs = 40,8233 kg = 7,3378 mm = 0,2889 inch |
| 55 lbs = 24,9476 kg = 12,0073 mm = 0,4727 inch | |

